

Adventure™ Grand Tourer 600 SDI



- L-XU design and ergonomics
 - Aluminium frame with pyramid construction
 - Wedge Bevelled Tunnel, WBT
 - Rear suspension shocks:
 - Center Arm: HP-Gas 36
 - Rear Arm: HP-Gas 36
 - Track: 500 x 3923 x 31,8, new pitch 72,6 mm
 - RCG-A + suspension
 - J-hook hitch
 - Multifunction analogue/digital instrumentation
 - Cooling radiator with electric fan
-
- A-LFS front suspension, sway bar
 - Ski shocks: 36 HP-Gas
 - CTRL II -skies
 - Straight handlebar, height adjustment system
 - High windshield, side wind deflectors
 - Removable rear seat standard with storage compartment
 - Heated passenger handgrips
 - Electric and rewind starter
 - Easy cleaning running boards
 - Easy open Top Access panel for daily inspections
 - Bigger cargo rack, fixation points for rope
 - LED -tail light

LYNX



Adventure™ Grand Tourer 600 SDI

Engine	Rotax 593 H.O. SDI
Carburetor/throttle body type	2 x Dellorto dia. 46
Lubrication	injection oil
Starting system	Electric + rewind starter
Drive pulley	TRA III
Driven pulley	QRS
Front suspension type	A-LFS
Front shock	HP-Gas, 36
Travel mm	225
Rear suspension	RCG-A
Rear shocks	HP-Gas, 36 / HP-Gas, SPA 36
Travel mm	340
Mass kg	286 (incl. oil + fluids)
Width / Length mm	1135 / 3230
Height (incl. windshield) mm	1330
Ski stance mm	1080
Track mm (W x L / H)	500x3923/32
Fuel tank /	45
Injection oil reservoir L	2,8
Ski type	CTRL II
Reverse	Mechanical Syncro 1+2+N+R
DESS	STD
Electric Start	STD
Current outlet	STD
Seat two passengers / backrest	STD / STD
Windshield	X-High

LYNX

