

Rave™ RE 600 HO E-TEC



- Advanced RE-X design and flexible ergonomics
- A-Force frame with Wedge Bevelled Tunnel (WBT)
- Narrow seat and fuel tank
- Wide and flat foot boards
- PPS suspension
- Rear suspension shocks:
 - Center Arm: TA 46 HLCR
 - Rear Arm: TA 46 HLCR
- Track: 380 x 3048 x 38 Rip Saw
- Racing Brakes / braided brake lines
- A-LFS front suspension
- Ski shocks: TA 36 HLC
- CTRL II -skies
- CroMo J-hook bar with riser block
- Wind deflectors for hands
- X -low windshield
- 1-up RE seat
- LED -taillight
- Suspension calibration: Mogul greedy

LYNX



Rave™ RE 600 HO E-TEC

Engine Rotax	593 H.O. E-TEC
Carburetor/throttle body type	2 x Dellorto dia. 46
Lubrication	Electric oil pump
Starting system	Rewind starter
Drive pulley	TRA III
Driven pulley	QRS
Front suspension type	A-LFS
Front shock	TA 36 HLC
Travel mm	242
Rear suspension	PPS-120
Rear shocks	TA 46 HLCR TA 46 HLCR
Travel mm	390
Mass kg	209 (incl. oil + fluids)
Width / Length mm	1245 / 2810
Height (incl. windshield) mm	1200
Ski stance mm	1080
Track mm (W x L / H)	380x3051/38
Fuel tank /	39
Injection oil reservoir L	3,7
Ski type	CTRL II
Reverse	RER
DESS	STD
Electric Start	OPT
Current outlet	OPT
Seat two passengers /	- / -
backrest	
Windshield	X-Low

LYNX

