

# RENEGADE

## 2010 RENEGADE® X®



### PACKAGE HIGHLIGHTS

- Rotax® 1200 4-TEC® engine
- REV-XR™ platform
- REV-XR glossy side panels
- Brembo racing brake with braided stainless-steel brake line
- Lightweight chromoly front suspension lower A-arm
- HPG™ Plus R aluminum front shocks with no-tool rebound adjuster
- KYB Pro 36 aluminum piggy-back rear shock with dual-speed compression adjusters
- Lightweight 15 x 137 x 1.25-inch RipSaw® track
- REV-XP™ X seat
- Riser block / handlebar wind deflectors / low windshield
- Multi-function digital gauge w/display
- Mechanical reverse
- Electric fuel gauge

### ENGINE CHOICE    COLOR CHOICE

Rotax 1200 4-TEC	White / White Deep Black
------------------	-----------------------------

### ENGINE

Engine	Rotax 1200 4-TEC
Engine details	Liquid-cooled, four-stroke D.O.H.C. dry sump
Cylinders	3
Displacement	1170.7 cc / 46.9 in <sup>3</sup>
Bore	91 mm / 3.6 in
Stroke	60 mm / 2.4 in
Max. engine speed	7800 RPM
Carburetion	EFI
Recommended fuel type	Regular unleaded
Min. octane	87
Fuel tank	40 liters / 10.6 gallons
Engine oil capacity	3.5 liters / 3.7 quarts
Exhaust system	Single head-pipe, baffle muffler

### POWERTRAIN

Drive clutch type	TRA™ IV
Driven clutch type	QRS
Engagement	2800 RPM
Small sprocket number of teeth	24
Large sprocket number of teeth	45
Drive sprocket number of teeth	8
Drive sprocket diameter	183 mm / 7.2 in
Brake system	Brembo racing brake with braided stainless-steel brake line

### FEATURES

Frame	REV-XR	Electric start	Standard	Tachometer	Standard	Windshield	250 mm / 10 in
Skis	Pilot™ 5.7	Reverse	Mechanical	Fuel gauge	Standard	Carbide runner	Standard
Seating	REV-XP X	Heated throttle lever	Standard	Temperature gauge	Optional	Hitch	Optional
Handlebar	Aluminum with J-hooks / Riser block (115 mm / 4.5 in)	Heated grips	Standard	Mirrors	Optional		
		Speedometer	Standard				

### SUSPENSION

Front suspension	Dual A-arm
Front shock	HPG Plus R
Front suspension max. travel	229 mm / 9 in
Rear suspension	SC™-5
Center shock	HPG Plus
Rear shock	KYB Pro 36
Rear suspension max. travel	406 mm / 16 in

### DIMENSIONS

Vehicle overall length	3110 mm / 122.4 in
Vehicle overall width	1217 mm / 47.9 in
Vehicle overall height	1110 mm / 43.7 in
Official dry weight	236 kg / 519 lb
Ski stance	1077 mm / 42.4 in
Ski overall length	1066 mm / 42 in
Ski width	145 mm / 5.7 in
Track nominal width	381 mm / 15 in
Track nominal length	3486 mm / 137 in
Track profile height	31.8 mm / 1.25 in

